



MATERIAL SAFETY DATA SHEET  
DUROCK ALFACING INTERNATIONAL LTD.

---

### 1. Chemical Product and Company Identification

Chemical Name: Indiana Limestone  
MSDS Date: June 2014

**Company Identification**  
DuROCK Alfacing International Ltd.  
101B Roytec Rd  
Woodbridge, On  
L4L 8A9

**Emergency Telephone Numbers**  
Health Emergency: 905-856-0133  
Spill Emergency: 905-856-0133

---

### 2. Composition/Information on Ingredients

| <u>Chemical Name</u> | <u>CAS REG NO.</u> | <u>Weight (%)</u> | <u>TLV(mg/m<sup>3</sup>)</u> | <u>LC<sub>50</sub>/LD<sub>50</sub></u> |
|----------------------|--------------------|-------------------|------------------------------|--|
| Silica Sand          | N/A                | 50-55             | Not listed                   | N/A                                    |
| Portland Cement      | N/A                | 30-35             | Not listed                   | N/A                                    |
| Microspheres         | N/A                | 3.0-3.5           | N/A                          | N/A                                    |
| Copolymer            | 108-05-4           | 3.5-4.0           | 10ppm                        | N/A                                    |

---

### 3. Hazardous Identification

Primary Routes of Exposure

Inhalation     Skin Absorption     Eye Contact     Ingestion     Skin Contact

Effects of Acute Exposure to Product

Breathing dust may cause nose, throat or lung irritation and choking. Prolonged or repeated exposure may cause lung injury including silicosis. Risk of injury depends on duration and level of exposure. May cause eye irritation and damage to cornea. May cause dry skin, redness, discomfort, irritation or burns. Ingestion of large amounts may cause intestinal distress.

Other Health Effects

Crystalline silica is a chemically inert, non combustible mineral. Prolonged exposure to respirable crystalline quartz may cause delayed lung injury. Pulmonary function may be reduced by inhalation. Smoking aggravates the effects of exposure.

---

### 4. First Aid Measures

Inhalation

Move victim to fresh air. Obtain medical attention for discomfort.

Eye Contact

Immediately flush eyes with running water for a minimum of 20 minutes or with an ophthalmic saline solution. Hold eyelids open during flushing. If irritation persists, repeat flushing. Obtain medical attention for abrasions.



DUROCK ALFACING INTERNATIONAL LTD.  
101B ROYTEC RD  
WOODBIDGE, ON  
L4L 8A9

PRODUCT: INDIANA LIMESTONE  
MSDS DATE: JUNE 2014

---

#### 4. First Aid Measures cont.

##### Skin Contact

Flush skin with running water and wash affected areas thoroughly with soap and water.

##### Ingestion

Rinse mouth with water. DO NOT INDUCE VOMITING but drink plenty of water. Obtain medical attention for discomfort.

If symptoms persist, contact a physician or other medical personnel.

---

#### 5. Fire Fighting Measures

Flash Point: N/A

Auto-Ignition Temperature: N/A

Lower Explosive Limit: N/A

Upper Explosive Limit: N/A

Unusual Hazards:N/A

Extinguishing Agents:N/A

---

#### 6. Handling and Storage

##### Storage Conditions

Avoid accidental release. Store dry and away from water.

##### Handling Procedures

N/A

---

#### 7. Personal Protection

##### Respiratory Protection

NIOSH/MSHA approved respirator if required.

##### Eye Protection

Safety glasses with side shields are recommended to prevent eye contact. Wearing contact lenses when using this product under dusty conditions is not recommended.

##### Hand Protection

Use gloves, shoes and protective clothing to prevent skin contact.

##### Engineering Controls (Ventilation)

Use local exhaust or general ventilation to maintain dust levels below exposure limits in workplaces with poor ventilation and dusty conditions.



---

## 8. Physical and Chemical Properties

State: Flowable powder  
PH: Alkaline  
Viscosity: None, powder  
Evaporation Rate (Bac\_1): Not measurable

---

## 9. Stability and Reactivity

### General

Product is stable but must be kept dry. Reacts with water.

### Incompatible Materials and Conditions to Avoid

Must be kept dry. Cement reacts in hydrofluoric acid producing corrosive gas. Silicates react with powerful oxidizers which may cause fires.

### Hazardous Decomposition

None for Cement. Crystalline silica dissolves in hydrofluoric acid and produces corrosive gas.

---

## 10. Toxicological Information

Acute Data: N/A  
Oral LD50 – rat: N/A  
Dermal LD50 – rabbit: N/A  
Skin irritation – rabbit: N/A  
Eye irritation – rabbit: N/A

---

## 11. Other Information

MSDS prepared by: DuROCK Alfacing International Limited  
101B Roytec Rd  
Woodbridge, On  
L4L 8A9

Supplier: DuROCK Alfacing International Limited  
101B Roytec Rd  
Woodbridge, On  
L4L 8A9

Manufacturer: DuROCK Alfacing International Limited  
101B Roytec Rd  
Woodbridge, On  
L4L 8A9