

Plus Finishes

Elastomeric Acrylic Textures

PRODUCT DESCRIPTION

DuROCK Plus Finishes are formulated with 100% acrylic emulsions designed especially for use in elastomeric wall coatings, providing outstanding exterior durability, as well as excellent elasticity and elongation properties that are required to bridge continually over cracks without wrinkling. Due to the low glass-transition temperature, these finishes are able to maintain flexibility across a broad range of temperatures.

Plus Finishes can be tinted to virtually any colour and are intended for application on vertical wall surfaces. These finishes are most effective when applied over rigid substrates (such as cement plasters and concrete), and can also be used with **DuROCK EIFS** and **Exterior Finish Systems**.

Plus Finishes are formulated to have excellent dirt-pick-up resistance, and superior water resistance as well as resistance to chalking. The dirt pick-up resistant chemistry of **Plus Finishes** enables the coating to maintain its attractive appearance, while providing superior resistance to the effects of acid rain, pollution and ultra-violet light. **Plus Finishes** also bead water, thereby washing away surface dirt. **Plus Finishes** are permeable to water vapour, which permits open vapour diffusion through wall assemblies.

DuROCK Plus Finishes are available in the following textures:

- | | | |
|---------------|------------|--------------------------|
| • Sand Coat | • Venetian | • Marble Coat |
| • Spacco | • Max Coat | • Marble Coat Fine |
| • Coarse Coat | • Grain | • Roll-On (Roller Grade) |

STORAGE & MIXING

Store **Plus Finishes** above 4°C (40°F) and below 40°C (104°F), off the ground and in a dry place away from direct sunlight. Under no circumstances shall **Plus Finishes** be permitted to freeze.

Using a stainless steel or corrosion resistant mixing blade and power drill, mix at 400 – 500 rpm, ensuring not to induce air into the product. Mix product until a uniform consistency is attained. Discard material that becomes stiff or hard.

APPLICATION & COVERAGE

Substrate must be clean, dry, and free of cracks or loose material. Surface and ambient temperatures must be at least 4°C (40°F) for a minimum of 24 hours, and must remain so until the **Plus Finishes** have dried. The surface shall be dry and firm to the touch before being exposed to ambient conditions. Do not apply **Plus Finishes** in direct sunlight at temperatures exceeding 30°C (86°F) and protect from winds exceeding 25 km/hr (15 mph) as well as precipitation for at least 24 hours.

Apply **Plus Finishes** with a stainless steel trowel, then float the material with either a stainless steel or plastic trowel to the required texture. The application must be continuous across wall areas, starting and ending at natural breaks in the surface, such as expansion joints, control joints, termination points, and corners. **Roll-On Plus** is applied with a medium pile paint roller.

DuROCK Plus Finishes are available in 19 L (4.18 gallons) pails (25-30 kg/pail depending on finish), yielding approximately 80 to 140 ft² (7 to 13 m²) per pail, depending on the texture selected. **Roll-On Plus** yields 37 to 46 m² (400 to 500 ft²) per coat.

TECHNICAL DATA

Technical data available upon request.

Refer to www.DuROCK.com for the most up-to-date version of this document.